



Care and cleaning for WST decorative coverings

01/15

A long beautiful appearance of WST decorative floors requires regular care and cleaning.

1. initial care:

Initial care is not required for WST decor flooring directly after installation if it has received a head sealant in accordance with the WST installation instructions and there is thus sufficient surface protection of the WST decor flooring. In the case of sustainable trades, the WST decor floor must be protected against soiling with felt cardboard, foil or similar. Please note that the floor is only chemically resistant after seven days.

2. Daily cleaning / maintenance cleaning:

2.1 WST decor floor in living areas without filler

Vacuum clean with a hoover if necessary, damp mop with warm water with the addition of commercially available neutral cleaning agents without the addition of lemon or orange fragrances. As the covering is permeable to water, make sure that only a little water penetrates the covering.

2.2 WST Decor floor with filler /additional seal

Clean by wet or damp mopping- preferably with hot water with the addition of commercially available neutral cleaning agents without added lemon or orange fragrances. Wipe with clean water. Absorb excess water with wipes.

3. stain removal:

Sticky dirt -such as chewing gum- should be removed immediately if possible. Fresh chewing gum can be embrittled with an icing spray and can then be removed with a brush. Stubborn stains that have not been removed for a long time usually cannot be removed without leaving residues. When using commercially available stain removers or solvents it is advisable to first carry out a test on an inconspicuous area! We cannot accept any guarantee for possible colour changes.

4 Basic cleaning:

Basic cleaning of the WST decor floor in commercially used areas may be necessary on a weekly basis depending on the amount of dirt. In residential areas, basic cleaning should be carried out 2 - 4 times a year depending on the amount of dirt. The use of cleaning machines is recommended for this purpose, whereby roller brushes should be used instead of disc brushes. Do not treat surfaces with high-pressure cleaners!

Commercially available acid or phosphate-containing basic cleaners in concentrated form can cause colour changes and the decomposition of the binder. The same applies to oxidising agents and solvents. We cannot accept any liability for any damage.

5 Re-sealing:

WST decorative floors can also be subsequently sealed. The prerequisite is a stain-free cleaned floor covering and sufficient drying time. Ask us for further information.

Conclusion

These cleaning and maintenance methods have proven themselves in commercial and industrial use. Nevertheless, from time to time special soiling occurs that cannot be removed with this method. In this case, please contact us, a manufacturer of cleaning and care products or a specialist company that specialises in the cleaning and care of cast resin floors.